

PERSONAL COMPUTER CAMERA WITH VARIOUS APPLICATIONS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a PC (Personal Computer) camera, in particular to a PC camera with various application which is capable of operating as a digital camera and a digital audio reproducing apparatus independently by separating from a PC.

2. Description of the Prior Art

In the present times, a PC (Personal Computer) camera is used for a video conference. The PC camera adopts a USB (Universal Serial Bus) standard in order to interface with a PC directly.

However, in the conventional technology, the PC camera can operate only when it is connected to the PC, and it only has a function for transmitting a photographed image to the PC.

Accordingly, the conventional PC camera can not be used as a camera after it is separated from the PC.

SUMMARY OF THE INVENTION

Therefore, it is an object of the present invention to provide PC camera with various application which can be used a digital camera and a digital audio reproducing apparatus independently by separating from a PC.

In addition, the present invention is capable of listening digital audio data by storing the digital audio data.

And, the present invention is capable of adjusting focus and brightness of the PC camera when it is independently used as the digital camera.

5 In addition, the present invention is capable of transmitting the image photographed by the PC camera or compressed the photographed image by a wireless communication method.

Therefore, an object of the present invention is to provide a PC camera for transmitting a photographed image to a PC by converting the photographed image
10 into a USB standard signal.

The PC camera comprises a view finder for recognizing direction and range of a photographing object, a memory for storing a photographed image and digital audio data, an image processing unit for transmitting a picture-processed photographing image signal to the PC in a video conference mode, storing the
15 picture-processed photographing image signal on the memory after compressing it in a digital camera mode, transmitting the compressed image signal stored on the memory to the PC in a still image transmission mode, a digital audio decoder for restoring the digital audio data stored on the memory into an original signal in a digital audio reproducing mode, a control unit for judging the video conference
20 mode, digital camera mode, still image transmission mode or digital audio reproducing mode in accordance with open/close of a lens cap and combination/separation with/from the PC and controlling the pertinent operation, and a backup battery unit for charging voltage provided from the outside in the video conference mode or still image transmission mode, and providing the
25 charged voltage as an operating voltage in the digital camera mode or digital audio

reproducing mode.

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG.1 is a block diagram illustrating a PC camera with various application according to the first embodiment of the present invention.

FIGs.2A and 2B illustrate an open/close state of a lens cap.

FIGs.3A through 3C illustrate a combination/separation state of the PC camera.

10 FIG.4 is a circuit diagram illustrating a backup battery unit of FIG.1.

FIG.5 is a block diagram illustrating a partial construction of the PC camera with various application according to the second embodiment of the present invention.

15 FIG.6 is a block diagram illustrating a PC camera with various application according to the third embodiment of the present invention.

FIG.7 is a construction profile illustrating a focus adjustment switch unit of FIG.6.

FIG.8 is a block diagram illustrating a focus adjustment reading unit of FIG.6.

20 FIG.9 is a wave gram illustrating an edge element value in focus adjustment reading of FIG.6.

FIG.10 is a block diagram illustrating a PC camera with various application according to the fourth embodiment of the present invention.

25 FIG.11 is a block diagram illustrating a brightness adjustment reading unit of FIG.10.

FIG.12 is a block diagram illustrating a PC camera with various application according to the fifth embodiment of the present invention.

FIGs.13A through 13C illustrate an earphone combination state of FIG.12.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, the present invention will now be described with reference to accompanying drawings in detail.

FIG.1 is a block diagram illustrating a PC camera with various application according to the first embodiment of the present invention, as depicted in FIG.1, PC camera with various application according to the embodiment of the present invention comprises a view finder 106 for recognizing direction and range of an photographing object, a lens unit 101 for concentrating light from a subject, a photographing unit 102 for converting the light about the concentrated image by the lens unit 101 into an electric signal, an image processing unit 103 for converting the electric signal of the photographing unit 102 into a digital signal and image-processing it in order to output the image-processed digital signal as it is in a video conference mode, and compress and store the image-processed digital signal at the press time point when a shutter 109 is pressed in the digital camera mode, a memory 107 for storing the digital image data compressed on the image processing unit 103 in the digital camera mode, a PC interface unit 104 for transmitting the image-processed digital signal to a host computer 105 in the video conference mode, transmitting the compressed image data stored on the memory 107 to the host computer 105 in the still image transmission mode, a first switch 110 for opening/closing a lens cap, a second switch 11 for detecting

combination/separation with/from the host computer 105, a control unit 108 for controlling the operation of the image processing unit 103 in order to perform the digital signal processing about the concentrated image in the video conference mode or digital camera mode, judging it as the video conference mode when the first and second switches are on state, judging it as the still image transmission mode for transmitting the concentrated still image to the host computer 105 when the first switch 110 is OFF and the second switch 111 is ON, and judging it as the digital camera mode for photographing the still image when the first switch 110 is ON and the second switch 111 is OFF, and a backup battery unit 112 for charging voltage provided through the PC interface unit 104 in the video conference mode or still image transmission mode and providing the charged voltage as operation voltage in the digital camera mode.

The PC interface unit 104 is constructed so as to input/output USB (Universal Serial Bus) standard data.

The first switch 110 is constructed so as to be ON when the lens cap is open as depicted in FIG.2A and so as to be OFF when the lens cap is closed as depicted in FIG.2B.

, the second switch 111 is installed inside of a groove 132 formed on the lower end portion of the PC camera as depicted in FIGs.3B and 3C so as to be ON when it is combined to a holder 131 in order to fix the PC camera as depicted in FIG.3A.

The operation and effect of the PC camera with various application according to the first embodiment of the present invention will now be described.

In the first embodiment of the present invention, the lens unit 101 concentrates the light from the subject, the photographing unit 102 converts it into

the electric signal, the image processing unit 103 converts the electric signal into the digital signal, accordingly image processing about the subject is performed as a frame unit.

First, in the video conference mode, the PC camera is combined to the holder 131, the second switch 111 is ON, and the first switch 110 is ON by opening the lens cap in order to photograph the subject.

Herein, the control unit 108 judges it as the video conference mode, and controls the image processing unit 103 so as to transmit the image-processed signal to the host computer 105 as the frame unit through the PC interface unit 104.

Accordingly, the host computer 105 processes the image transmitted from the PC camera, displays the image on a screen of a display unit (not shown) such as a monitor, and transmits the image to remote place by using a communication unit (not shown) such as a modem in case of need.

And, the focus and brightness of the captured image can be adjusted by using a program installed on the host computer 105.

For example, in the focus adjustment, when the subject image displayed on the screen of the display unit (not shown) is too far, the focus about the subject can be adjusted by decreasing the range of the image for converting into the electric signal on the photographing unit 102, in addition, in the brightness adjustment, when the subject image is too dark, the brightness of the subject image can be adjusted by adjusting the brightness on the image processing unit 103.

In addition, when the PC camera is separated from the holder and the second switch 111 is OFF, the control unit 108 judges it as a standby state for the digital camera mode.

Herein, when the user opens the lens cap, the first switch 110 is ON, the control unit 108 judges it as the digital camera mode, the image data image-processed orderly through the lens unit 101, photographing unit 102, image processing unit 103 is temporarily stored on the memory 107.

5 According to this, when a user presses the shutter 109 while watching the subject through the view finder 106 after determining the range of the photographing subject, the control unit 108 informs it to the image processing unit 103, the image processing unit 103 reads image information in the press time point of the shutter 109 from the memory 107 and compresses it, and stores it on
10 the memory 107.

The operation for storing the compressed image information is performed repeatedly whenever the user presses the shutter 109.

After that, when the user combines the PC camera to the holder in a state which lens cap is closed in order to edit or print the photographed still image, the
15 first switch 110 is OFF, the second switch 111 is ON, accordingly the still image transmission mode is set.

Herein, the user operates the program installed on the host computer 105 for image-processing, and transmits the control signal for the still image transmission to the PC camera.

20 According to this, the control unit 108 controls the image processing unit 103 so as to transmit the still image, the image processing unit 103 reads the compressed image information stored on the memory 107, and transmits it to the host computer 105 through the PC interface unit 104.

The operation for judging the combination/separation between the PC
25 camera and host computer 105 by the ON/OFF state of the second switch 111 is

described above, however it is also possible to judge the combination/separation between the PC camera and host computer 105 by detecting a reception signal (for example, USB standard signal) through the PC interface unit 104.

Herein, the present invention can be constructed so as to judge the digital camera mode switch by using the method for detecting the reception signal (for example, USB standard signal) from the PC and the other method for judging the ON/OFF state of the second switch 111 at the same time.

In other words, when the PC camera is separated from the host computer 105, the PC camera is automatically switched into the digital camera mode.

In the present invention, the video conference mode or digital camera mode or digital audio reproducing mode is selected in accordance with the ON/OFF of the first switch 110 operated by the open/close state of the lens cap and ON/OFF of the second switch 111 operated by the combination/separation state of the camera from the holder 131, in addition a plurality of operating buttons for a mode switch and a certain function select etc can be additionally constructed in the present invention.

For example, a mode select switch for selecting the one mode among the video conference mode, digital camera mode, digital audio reproducing mode is comprised, and function buttons for a music select, audio volume adjustment, reproducing start etc. in the digital audio reproducing mode are comprised.

And, the video conference mode does not require the operation power, but the operation power is required for operating as the digital camera mode.

Accordingly, in the first embodiment of the present invention, the backup battery unit 112 performs the charge operation in the combination state with the host computer 105, and provides the charge voltage as the operation voltage in

the separation state from the host computer 105.

Herein, the backup voltage is provided to the host computer 105 through the PC interface unit 104.

As depicted in FIG.4, the backup battery unit 112 comprises two switching diodes D1, D2 and a battery, in the video conference mode or still image transmission mode, the switching diode D2 is OFF and switching diode D1 is ON, the backup power is provided to a battery, accordingly it is charged. In the digital camera mode, the switching diode D1 is OFF and switching diode D2 is ON, the charge voltage of the battery is provided as the operation voltage through the switching diode D2.

An additional power port for providing backup voltage from the outside can be comprised or an additional battery can be installed in the present invention.

In the present invention, the memory 107 for storing the photographed image information is described in the first embodiment, as depicted in FIG.5, in addition, an additional memory card 151 can be comprised in the second embodiment of the present invention.

In other words, in the second embodiment of the present invention, the additional memory card 151 for storing the compressed image information temporarily stored on the memory 107 and a gate array 152 for inputting/outputting the image information between the image processing unit 103 or the memory 107 and the memory card 151 are comprised.

The operation of the second embodiment of the present invention will now be described.

Although the memory card 151 installed, the operation about the video conference mode, still image transmission mode, digital camera mode is same

with the first embodiment of the present invention.

Accordingly, when the digital camera mode is set and the user records the subject, the image information compressed on the image processing unit 103 is stored on the memory 107.

5 After that, the compressed image information stored on the memory 107 is stored on the memory card 151 through the gate array 152.

Herein, the storing of the compressed image information on the memory card 151 can be performed automatically when a certain key is selected or memory card 151 is installed.

10 And, in the third embodiment of the present invention, when the PC camera is used as the digital camera, the focus can be adjusted with manual operation.

In other words, as depicted in FIG.6, the third embodiment of the present invention having the same construction with the first embodiment comprises a
15 focus adjustment unit 161 for adjusting a focus of the lens unit 101, a focus adjustment reading unit 162 for extracting the edge element of the subject from the image frame of the image processing unit 103, reading the focus adjustment, and transmitting the reading result of the control unit 108, and a display unit 163 for displaying the focus adjustment result transmitted from the image processing unit
20 103 by the control of the control unit 108.

As depicted in FIG.7, the focus adjustment unit 161 comprises a switch 171 having a saw tooth shape for moving the position of the lens unit 101, a switch 172 having a saw tooth shape rotated by the rotation of the switch 171, a screw 173 installed on the center of the switch 172 for moving the lens unit 101 back and
25 forth by rotating interlocked with the rotation of the switch 172, and a detector 174

for detecting the rotation of the switches 171, 172 or screw 173 and transmitting the detect result to the control unit 103.

Herein, the detector 174 can be constructed as a rotary encoder.

When the control unit 108 detects the focus adjustment of the focus adjustment unit 161, it transmits the image frame after the focus adjustment to the focus adjustment reading unit 162, and at the same time it controls the image processing unit 103 in order to display the reading result of the focus adjustment reading unit 162 on the display unit 163.

As depicted in FIG.8, the focus adjustment reading unit 162 comprises a high-band filter 181 for extracting the edge element of the subject by performing the high-band filtering of the image frame from the image processing unit 103, an adder 182 for adding the edge element value on the high-band filter 181, and a comparator 183 for comparing the result value of the adder 182 with a certain set value and transmitting the comparing result (for example, a high signal is transmitted when the result value is bigger than a certain set value) is transmitted to the control unit 108.

The display unit 163 is constructed as a 7-segment LED or LCD.

The operation and effect of the third embodiment according to the present invention will now be described.

When the user rotates the switch 171, the lens unit 101 moves back or forth by the rotation of the switch 172 having the screw 173, the detector 174 detects the rotation of the switches 171, 172 or screw 173 and transmits it to the control unit 108.

Herein, when the image concentrated on the lens unit 101 is converted into the electric signal on the photographing unit 102, the image processing unit

103 performs the image processing by converting it into the digital signal.

According to this, the high-band filter 181 of the focus adjustment reading unit 162 performs the high-band filtering of the image frame from the image processing unit 103, and extracts the edge element of the subject, the adder 182
5 adds the all edge element values, the comparator 183 compares the added value with a certain set value, and the comparing result is transmitted to the control unit 108.

Herein, when a low signal is inputted from the focus adjustment reading unit 162, the control unit 108 judges it the focus is not adjusted, and the control
10 unit 108 the image processing unit 103 in order to display it.

According to this, the image processing unit 103 transmits the information for displaying a focus non-adjustment state to the display unit 163.

On the contrary, when the high signal is inputted from the focus adjustment reading unit 162, the control unit 108 judges it the focus is adjusted,
15 and the control unit 108 controls the image processing unit 103 in order to display it.

According to this, the image processing unit 103 transmits the information for displaying the focus adjustment state to the display unit 163.

Fog example, the output vale of the adder 182 can be displayed as the
20 waveform diagram of FIG.9 in accordance with the focus adjustment, when the focus is adjusted, the output value of the adder 182 can be the highest.

Herein, the display unit 163 displays the focus adjustment result with a number or character.

Accordingly, the user adjusts the focus while watching the number or
25 character displayed on the display unit 163.

Until now the technology for adjusting the focus with manual operation is described. Meanwhile, in the fourth embodiment of the present invention, the brightness can be adjusted with manual operation.

In other words, as depicted in FIG.10, the fourth embodiment of the present invention having same construction with the first embodiment comprises a brightness adjustment unit 190 for adjusting the brightness of the image in photographing, and a brightness adjustment reading unit 200 for finding the difference of the consecutive image frame inputted from the image processing unit 103 before and after the brightness adjustment. When the brightness adjustment unit 190 operates and transmitting the result value to the control unit 108.

The brightness adjustment unit 190 can be constructed as a slide switch.

When the brightness control unit 190 operates, the control unit 108 judges it as a brightness adjustment mode, transmits the image frame before and after of the brightness adjustment to the brightness adjustment reading unit 200, and at the same time controls the image processing unit 103 in order to display the result value from the brightness adjustment reading unit 200 on the display unit 163.

As depicted in FIG.11, the brightness adjustment unit 200 comprises registers 201, 202 for storing the consecutive two frames, and the comparator 203 for comparing the image frames stored on the registers 201, 202 and transmitting the differences to the control unit 108.

The operation of the fourth embodiment according to the present invention will now be described.

When the user adjusts the position of the slide switch comprised in the brightness adjustment unit 190, the control unit 108 judges it as the brightness adjustment mode, and controls the image processing unit 103 in order to transmit

the image frames before and after the brightness adjustment to the brightness adjustment reading unit 200.

Herein, when the image frame before the brightness adjustment is transmitted, it is stored on the register 201, again when the image frame after the brightness adjustment is transmitted, the image frame stored on the register 201 is stored on the register 202, and the newly transmitted image frame is stored on the register 201.

According to this, the comparator 203 compares the image frames stored on the registers 201, 202, and transmits the differences to the control unit 108.

Herein, the control unit 108 controls the image processing unit 103 in order to display the differences transmitted from the brightness adjustment reading unit 200 on the display unit 163.

Accordingly, the user adjusts the image brightness in photographing by adjusting the slide switch comprised in the brightness adjustment unit 190 while watching the number displayed on the display unit 163.

Herein, comparing between the two image frames is performed about a certain same region corresponding to each other.

Until now, the method for comparing the consecutive two image frames is described, the brightness of the image can be adjusted by storing a certain set brightness value in advance and comparing the brightness value of the image frame with the certain set value in photographing.

In addition, in the third and fourth embodiments of the present invention, the focus adjustment reading unit 162 and brightness adjustment reading unit 200 are comprised additionally, but it is also possible to construct the focus adjustment reading unit 162 and brightness adjustment reading unit 200 inside of the image

processing unit 103, in this case the control unit 107 receiving the reading result judges the focus and brightness adjustment, and controls the image processing unit 103 in order to display it on the display unit 163.

In this case, the focus and brightness can be adjusted automatically by the control of the control unit 107.

And, in the fifth embodiment of the present invention, digital audio data can be reproduced.

Herein, the digital audio data will now be described with an example of MP3 data.

In other words, as depicted in FIG.12, the fifth embodiment of the present invention having the same construction with the first embodiment comprises an image processing unit 103 for storing temporarily the MP3 data transmitted from the host computer 105 on the memory 107, a switch 213 for switching ON/OFF the MP3 mode, a MP3 decoder 211 for restoring the MP3 data transmitted through the gate array 152 into the original signal when the lens cap is closed and the switch 213 is ON, and a digital/analog converter 212 for converting the digital signal from the MP3 decoder 211 into the analog signal and outputting it to an earphone.

The operation of the fifth embodiment of the present invention will now be described.

First, when the PC camera is combined to the host computer 105, the user transmits the MP3 data downloaded from the internet to the PC camera.

After that, when the user closes the lens caps after using the digital camera, the PC camera is in the switch standby state for the MP3 mode or still image transmission mode, when the MP3 mode switch 213 is OFF. As depicted in FIG.1, the operation voltage from the backup battery unit 112 is cut off.

After that, when the MP3 mode switch 213 is ON. The gate array 152 reads the MP3 data stored on the memory 107 and transmits it to the MP3 decoder 211.

Herein, the MP3 decoder 211 decodes the MP3 data and outputs the original digital signal.

According to this, the digital/analog converter 212 converts the digital signal into the analog signal, outputs it to the earphone, accordingly the user can listen the MP3 music.

Herein, when the MP3 mode switch 213 is ON, the decoding operation is performed, and it is also possible to listen request music with select volume by pressing buttons for selecting music, starting the reproducing, adjusting the volume etc.

In the present invention, the MP3 data is stored on the memory 107, it is also possible to comprise an additional memory card 151 for expanding the storage capacity.

In addition, when the switch 213 is ON in the lens cap closed state, the present invention is switched into the MP3 mode, and it is also possible to switch into the MP3 mode automatically when the earphone is connected.

For example, as depicted in FIGs.13A through 13C, when the earphone is inserted into a jack 220 installed on the side surface of the PC camera, the switch 221 installed inside the jack 220 is ON, and the control unit 108 switches into the MP3 mode automatically.

Meanwhile, until now the method for operating the digital camera mode and MP3 mode by turns is described, it is also possible to listen MP3 music while photographing.

In this case, when the MP mode switch is ON and the earphone is connected, the digital camera mode and MP3 mode can be performed at the same time.

In addition, the present invention can comprises an additional wireless communication unit for transmitting the image photographed with the above-mentioned method and the compressed image stored on the memory unit to the host computer.

In other words, the present invention can be constructed to transmit the image photographed in the video conference mode or digital camera mode to the host computer 105 by comprising the wireless communication unit and converting the photographed image into the wireless signal.

In this case, it is possible to reproduce the MP3 data by receiving it by the wireless communication.

And, in the above-mentioned embodiment, the display unit 163 is constructed so as to display simple character or number in order to reduce the manufacture cost, but it is also possible to comprise an additional LCD for watching the photographed image.

In this case, the focus and brightness can be adjusted by using the additional LCD.